



PESF-H158-1-01

	电压	电流	输入功率	转矩	转速	输出功率	效率	时间
序号	V	A	W	N.m	rpm	W	%	S
1	48.13	2.395	115.3	0.11	411.3	4.823	4.2	0.000
2	48.13	3.156	151.9	1.19	409.8	51.14	33.7	2.703
3	48.13	5.088	244.9	3.40	405.5	144.5	59.0	4.406
4	48.13	7.485	360.3	5.79	400.7	242.8	67.4	6.109
5	48.13	10.21	491.3	8.44	396.2	350.1	71.3	7.813
6	48.13	12.75	613.6	12.11	389.7	494.0	80.5	9.516
7	48.13	16.03	771.7	15.35	384.5	617.9	80.1	11.22
8	48.13	18.84	906.6	19.53	377.7	772.4	85.2	12.92
9	48.13	22.41	1079	23.10	371.8	899.2	83.4	14.63
10	48.13	26.58	1279	27.06	365.7	1036	81.0	16.33
11	48.13	30.17	1452	31.73	358.1	1190	81.9	18.03
12	48.13	33.41	1608	35.56	352.9	1314	81.7	19.73
13	48.13	35.25	1697	40.18	328.5	1382	81.4	21.44
14	48.13	35.00	1685	44.00	297.4	1370	81.3	23.14
15	48.13	34.91	1680	48.11	265.1	1335	79.5	24.84
16	48.13	34.75	1673	52.82	228.3	1263	75.5	26.55
17	48.13	34.63	1667	56.87	206.1	1227	73.6	28.25
18	48.13	34.55	1663	61.21	179.6	1151	69.2	29.95
19	48.14	34.43	1658	64.55	163.4	1104	66.6	31.66
20	48.13	34.30	1651	67.76	149.5	1061	64.2	33.36
21	48.13	34.19	1646	71.82	130.1	978.3	59.5	35.06
22	48.13	34.07	1640	74.34	119.9	933.2	56.9	36.77
23	48.13	34.04	1638	76.96	108.0	870.2	53.1	38.47
24	48.13	33.95	1634	79.14	100.0	828.6	50.7	40.17
25	48.13	33.90	1632	80.57	93.9	792.1	48.5	41.88
26	48.13	26.34	1268	82.64	47.2	408.4	32.2	43.58